

VK Multimedia Information Systems



Mathias Lux, mlux@itec.uni-klu.ac.at

Dienstags, 16.00 Uhr c.t., E.1.42



This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 2.0 License. See <http://creativecommons.org/licenses/by-nc-sa/2.0/at/>

Results



<http://www.uni-klu.ac.at>

- Co-occurrence
- LSA

Retrieval Evaluation: Agenda



<http://www.uni-klu.ac.at>

- **Retrieval Evaluation**
- The Lucene Search Engine
- Exercise 04




Retrieval Evaluation: Motivation



<http://www.uni-klu.ac.at>

- Compare **objectively** different
 - Search engines
 - Models & Weighting Schemes
 - Methods & Techniques
- Scope
 - Academic
 - Commercial & Industrial
- Different aspects
 - Runtime, Retrieval performance



Retrieval Evaluation



<http://www.uni-klu.ac.at>

- Comparability issues:
 - Test collections
 - Experts assessing retrieval performance
 - Metrics
 - What's good? / What's bad?
- Overall problem:
 - What is relevant?


Metrics: Precision & Recall



<http://www.uni-klu.ac.at>

Within a document collection D
with a given query q

- $|R|$.. num. of relevant docs
- $|A|$.. num. of found docs
- $|R_a|$.. num. found & relevant



Metrics: Precision



<http://www.uni-klu.ac.at>

$$\text{Precision} = \frac{|Ra|}{|A|} = \frac{\text{found relevant docs}}{\text{found docs}}$$

- Gives % how many of the actual found documents have been relevant
- Between 0 and 1
 - Optimum: 1 ... all found docs are relevant

Metrics: Recall



<http://www.uni-klu.ac.at>

$$\text{Recall} = \frac{|Ra|}{|R|} = \frac{\text{found relevant docs}}{\text{relevant docs}}$$

- Gives % how many of the actual relevant documents have been found
- Between 0 and 1
 - Optimum: 1 ... all relevant docs are found

Metrics: Precision & Recall



<http://www.uni-klu.ac.at>

- With a query only 1 document has been found, but this one is relevant (100 would be relevant):
 - Precision & Recall
 - **Precision = 1**
 - **Recall = 0,01**

Metrics: Precision & Recall



<http://www.uni-klu.ac.at>

- With a query all documents of D have been found (5% of D would be relevant)
 - Precision & Recall?
 - **Precision = 0,05**
 - **Recall = 1**

Example



<http://www.uni-klu.ac.at>

- $D = \{D00, D01, \dots D99\}$
- Query 1:
 - Result Set 1: **{D2, D14, D25, D76, D84, D98}**
 - Relevant Docs {D1, D2, D14, D22, D23, D25, D84, D89, D90, D98}
- Query 2:
 - Result Set 1: **{D10, D14, D60, D63, D77, D95}**
 - Relevant Docs {D10, D14}

Recall vs. Precision Plot



<http://www.uni-klu.ac.at>

- Assumption:
 - Result list is sorted by descending relevance
 - User investigates result list linearly
 - Precision and Recall change
- Approach:
 - Map different states to graph


Recall vs. Precision Plot



<http://www.uni-klu.ac.at>

01. d123 *	06. D9 *	11. d38
02. d84	07. d511	12. d48
03. d56 *	08. d129	13. d250
04. d6	09. d187	14. d113
05. d8	10. d25 *	15. d3 *

$R_q = \{d3, d5, d9, d25, d39, d44, d56, d71, d89, d123\} \rightarrow 10$



Recall vs. Precision Plot




<http://www.uni-klu.ac.at>

- | | | |
|------------|-----------|----------|
| 01. d123 * | 06. D9 * | 11. d38 |
| 02. d84 | 07. d511 | 12. d48 |
| 03. d56 * | 08. d129 | 13. d250 |
| 04. d6 | 09. d187 | 14. d113 |
| 05. d8 | 10. d25 * | 15. d3 * |

$$\text{Recall} = \frac{|Ra|}{R} = \frac{1}{10}$$

$$\text{Precision} = \frac{|Ra|}{A} = \frac{1}{1}$$



Recall and Precision




<http://www.uni-klu.ac.at>

01. d123 *	06. D9 *	11. d38
02. d84	07. d511	12. d48
03. d56 *	08. d129	13. d250
04. d6	09. d187	14. d113
05. d8	10. d25 *	15. d3 *

$$\text{Recall} = \frac{|Ra|}{R} = \frac{2}{10}$$

$$\text{Precision} = \frac{|Ra|}{A} = \frac{2}{3}$$




Recall and Precision



<http://www.uni-klu.ac.at>

01. d123 *	06. D9 *	11. d38
02. d84	07. d511	12. d48
03. d56 *	08. d129	13. d250
04. d6	09. d187	14. d113
05. d8	10. d25 *	15. d3 *




Recall and Precision



<http://www.uni-klu.ac.at>

01. d123 *	06. D9 *	11. d38
02. d84	07. d511	12. d48
03. d56 *	08. d129	13. d250
04. d6	09. d187	14. d113
05. d8	10. d25 *	15. d3 *




Recall and Precision



<http://www.uni-klu.ac.at>

01. d123 *	06. D9 *	11. d38
02. d84	07. d511	12. d48
03. d56 *	08. d129	13. d250
04. d6	09. d187	14. d113
05. d8	10. d25 *	15. d3 *



F-Measure



<http://www.uni-klu.ac.at>

$$E(j) = 1 - \frac{1 + b^2}{\frac{b^2}{\text{recall}(j)} + \frac{1}{\text{precision}(j)}}$$

$F(j) = 1 - E(j)$... van Rijsbergen

- Lower values -> lower performance
- If $b=1$, $F(j)$ is average
- If $b=0$, $F(j)$ is precision
- If $b=\text{inf}$, $F(j)$ is recall
- $b=2$ is a common choice

Mean Average Precision (MAP)



<http://www.uni-klu.ac.at>

- Find average precision for each query
- Compute mean AP over all queries
 - Macroaverage: All queries are considered equal
- For average recall-precision curves
 - Average at standard recall points

Mean Average Precision (MAP)



<http://www.uni-klu.ac.at>

Example: Query Q1:

1. D12 (relevant) -> Precision: 1
2. D61
3. D39 (relevant) -> Precision: 2/3
4. D75 (relevant) -> Precision: 3/4
5. D66
6. D14 (relevant) -> Precision: 4/6
7. D52
8. D33 (relevant) -> Precision: 5/8

- Average Precision: $(1 + 2/3 + \dots) / 5 = 0.742$

Mean Average Precision (MAP)



<http://www.uni-klu.ac.at>

- Compute MAP:
 - Q1: 0,742
 - Q2: 0,633
 - Q3: 0,874
 - Q4: 0,722
- $MAP = (0,742 + 0,633 + ..) / 4 = 0,743$

$$AP(q) = \frac{1}{N_R} \sum_{n=1}^{N_R} P_q(R_n), \quad MAP = \frac{1}{|Q|} \sum_{q \in Q} AP(q),$$

src. Deselaers, T., Keyzers D., and Ney H., "Features for Image Retrieval: An Experimental Comparison", Information Retrieval, vol. 11, issue 2, Springer 2008.

Precision @ 10



<http://www.uni-klu.ac.at>

- Precision for the first 10 results
- Measures the quality of the first page
- Motivated by
 - Subjective impression that they all should be relevant
 - Fact that many people examine only first page

Error classification rate



<http://www.uni-klu.ac.at>

- Instance based learning
 - First result gives the class
- Inverse Precision @ 1

$$ER = \frac{1}{|Q|} \sum_{q \in Q} \begin{cases} 0 & \text{if the most similar image is relevant} \\ 1 & \text{otherwise} \end{cases}$$

src. Deselaers, T., Keyzers D., and Ney H., "Features for Image Retrieval: An Experimental Comparison", Information Retrieval, vol. 11, issue 2, Springer 2008.

Test Collections & Initiatives



<http://www.uni-klu.ac.at>

- Aim:
 - Provide data, topic & results
- Prominent Initiatives
 - Text Retrieval Conference (TREC)
 - Initiative for the Evaluation of XML Retrieval (INEX)
 - Cross Language Evaluation Forume (CLEF)

The TREC Collection



<http://www.uni-klu.ac.at>

- Aim: Support IR Research on big data collections with
 - Test collection
 - Uniform measures and methods
 - Platform for comparison & challenges
- TREC collection size increases steadily
- Several different tracks:
 - Ad hoc, Web, Blog, Confusion, Genomics Track, Question Answering, Spam, Terabyte
- Examples:
 - Spam: ~ 91.000 messages (300 MB zipped)
 - Ad hoc has 5 sets:
 - e.g. Disk 5: 260.000 documents (1 GB zipped)

Summary: Evaluation



<http://www.uni-klu.ac.at>

- Lots of measures exist besides Precision & Recall
- Selection based on Use Case & Scenario
- Initiatives & Collections allow comparison
- Also user centered evaluation methods exist
- collections & initiatives are criticized:
 - Handling of outliers, significance of differences, ...

Retrieval Evaluation: Agenda



<http://www.uni-klu.ac.at>

- Retrieval Evaluation
- **The Lucene Search Engine**
- Exercise 04



Lucene



<http://www.uni-klu.ac.at>

- A **Java** text search engine
 - .NET Implementation exists
 - Also used in PHP, etc.
- Initiated by Doug Cutting
 - Now paid by Yahoo!

- Implements an **inverted list**
 - Stores term -> document
 - Per field (e.g. title, content, ...)
 - And additional information (count, position, length, etc.)
 - File format & storage.
- Preprocesses input
 - Stemming, etc.
- Provides search & index update
 - Query, Ranking

Inverted list example ...



<http://www.uni-klu.ac.at>

- | | |
|-----------------------------|--------------------|
| 1. hello world | ● hello -> 1, 2, 3 |
| 2. hello bob | ● world -> 1, 4, 5 |
| 3. hello! say hello to bob. | ● bob -> 2, 3, 5 |
| | ● say -> 3 |
| 4. around the world | ● to -> 3 |
| 5. bob's world | ● around -> 4 |
| | ● the -> 4 |

even better:

hello (3 docs, 4 occ.) ->

1 (pos. 0), 2 (pos 0), 3 (pos. 0, pos. 12)

Inverted list example ...



<http://www.uni-klu.ac.at>

- hello -> 1, 2, 3
- world -> 1, 4, 5
- bob -> 2, 3, 5
- say -> 3
- to -> 3
- around -> 4
- the -> 4
- IDF
 - # of documents known
 - Size of corpus known
- TF
 - # of occurrences known
- Other stats
 - Length of document
 - Avg. length of docs
 - etc.

Lucene: Basic Usage



<http://www.uni-klu.ac.at>

Let lucene-{version}.jar and lucene-demos-{version}.jar be in your classpath

- To index files type:
 - `java org.apache.lucene.demo.IndexFiles [dir]`
- To search in the index type:
 - `java org.apache.lucene.demo.SearchFiles`

Lucene: Queries



<http://www.uni-klu.ac.at>

- Lucene has an extensive query parser
 - Parses text to internal representation
- Lucene supports several types of queries
 - Field based: title:"multimedia information"
 - Boolean clauses: multimedia AND image
 - Wildcards: te?t OR te*t
 - Fuzzy search: roam~ (e.g. *foam* and *roams*)
 - Proximity search: "java apache"~10
 - Term boosting: java^4 apache

Lucene File Format



<http://www.uni-klu.ac.at>

- Definitions:
 - An index contains a sequence of documents.
 - A document is a sequence of fields.
 - A field is a named sequence of terms.
 - A term is a string.
- Lucene uses
 - different types of fields:
 - stored, indexed, tokenized
 - Sub-indexes (segments, upon insertion)

Lucene: Usage



<http://www.uni-klu.ac.at>

- IndexWriter
 - Writes documents to the index
 - Uses Analyzer
- IndexSearcher
 - Searching documents in an index
 - Same Analyzer as for indexing needed
 - A Hits object is returned
- Document
 - Groups fields to logical unit

Lucene: Features



<http://www.uni-klu.ac.at>

- It's really fast & stable
 - Even compared to commercial products
- Handles multiple indexes
 - MultiReader, distributed search
- Has strong development support
 - Yahoo! & Apache (top level project)
- Lots of Stemmers, Tokenizers, etc.
 - English, German, Korean, Chinese, ...

Lucene: Projects & Tools



<http://www.uni-klu.ac.at>

- Nutch
 - Open source internet search engine
- Lucene .NET
 - Source code port to .NET
- Solr
 - Search server supporting web services, REST, ..
- Luke
 - GUI index management tool

Luke Demo ...



<http://www.uni-klu.ac.at>

Luke - Lucene Index Toolbox, v 0.8 (2008-02-08)

File Tools Settings Help

Overview Documents Search Files Plugins

Index name: **C:\Temp\index** [Re-open] [Close]

Number of fields: **3**

Number of documents: **10**

Number of terms: **11342**

Has deletions?: **No**

Index version: **1205851672503**

Last modified: **Tue Mar 18 15:47:52 CET 2008**

Directory implementation: **org.apache.lucene.store.FSDirectory**

Select fields from the list below, and press button to view top terms in these fields. No selection means all fields.

Available Fields: **<contents>** **<modified>** **<path>** [Show top terms >>]

Number of top terms: **50**

Hint: use Shift-Click to select ranges, or Ctrl-Click to select multiple fields (or unselect all).

Top ranking terms. (Right-click for more options)

No	Rank	Field	Text
1	6	<contents>	lucene
2	6	<contents>	apache
3	5	<contents>	2
4	5	<contents>	http
5	5	<contents>	s
6	5	<contents>	1
7	5	<contents>	3
8	5	<contents>	c
9	5	<contents>	4
10	4	<contents>	8
11	4	<contents>	7

Index name: **C:\Temp\index**

Retrieval Evaluation: Agenda



<http://www.uni-klu.ac.at>

- Retrieval Evaluation
- The Lucene Search Engine
- **Exercise 04**



Exercise 04



<http://www.uni-klu.ac.at>

- Retrieval Evaluation
 - Collection of 35 documents
 - Query and unsorted list of relevant documents - R
 - Ranked lists of 2 different search engines (A1 & A2)
- Your task
 - Compute precision and recall
 - Draw precision vs. recall plot
 - Compare A1 and A2 based on your findings

Don't forget!



<http://www.uni-klu.ac.at>

- Send me your results!